

RESCUE® Motors Permanent Split Capacitor Direct Drive Fan & Blower, 5.6" Diameter, Open, Air Over




APPLICATIONS:

Commercial and Residential Air Handlers and Furnaces. Can replace a range of horsepower applications and a variety of mounting styles.

FEATURES:

- Extended Mounting Studs
- Suitable for Use With 370V Capacitors
- Class B Insulation
- 36" Leads
- High Efficiency Design
- Includes Side Shell Holes For Rheem®† Units
- Continuous Duty, Air Over
- Reversible Rotation
- Automatic Reset Thermal Overload Protector
- 2.5" Diameter Hub Rings Included
- **Discount Symbol DS-3HAC**



HP	RPM	Voltage	Catalog Number	List	Cool Speed Tap	Heat Speed	Bearings	Cap. MFD	Amps	Shaft N	Base XD	Shell XI	Total C	Ship Wt.	Notes
1/3	825	208-230	5469	\$218	Med-Hi	High	SAB	7.5	2.4	2.2		4.6	6.7	17	H40
1/4					Med-Low	Med-Hi		7.5	1.7						
1/8					Low	Med-Low		7.5	0.9						
1/2	1075	115	5460	\$148	High	Med-Hi	SAB	12.5	7.3	5.0	5.4	4.8	9.8	19.74	H23,H40
1/3					High	Med-Low		7.5	6.9						
1/4					Med-Hi	Med-Low		7.5	5.5						
1/5					Med-Low	Low		7.5	3.6						
1/6					Low	Low		7.5	2.8						
1/2	1075	208-230	5461	\$151	High	Med-Hi	SAB	10	3.6	5.0	5.4	4.8	9.8	14.58	H23,H40
1/3					High	Med-Low		5	6.9						
1/4					Med-Hi	Med-Low		5	5.5						
1/5					Med-Low	Low		5	3.6						
1/6					Low	Low		5	2.8						
3/4	1075	115	5470	\$177	High	Med-Hi	Ball	20	8.1	5.0	6.6	6.1	11.6	18.13	H40
1/2					High	Med-Low		10	6.6						
1/3					Med-Hi	Med-Low		10	4.6						
1/4					Med-Low	Low		10	3.8						
1/5					Low	Low		10	3.1						
3/4	1075	208-230	5471	\$181	High	Med-Hi	Ball	20	4.1	5.0	6.6	6.1	11.6	16	H40
1/2					High	Med-Low		10	3.7						
1/3					Med-Hi	Med-Low		10	2.5						
1/4					Med-Low	Low		10	1.8						
1/5					Low	Low		10	1.7						

Note H23 For 1/3 To 1/6 HP, if more air flow is needed, a 7.5 MFD capacitor may be used

Note H40 Screws For Shell Mounting Included In Carton

† All marks shown within this document are properties of their respective owners.

Revised — August 2016