






Features:

- Maximum abnormal pressure (MAP): 700 psig, 48 bar
- Continuous operating temperature (COT): -40°F/300°F, -40°C/149°C
- Compatible with all CFC, HCFC and HFC refrigerants and oils
- UL/cUL Recognized, Conforms to Pressure Equipment Directive 97/23/EC
- Forged brass body
- Corrosion resistant stem suitable for refrigerants and other industrial fluids


NPTFE Inlet to Flare

NPTFE Inlet to Solder

Solder to Solder

NPTFE Inlet to Flare

Part Number	NPTFE A		Flare B		C		D		E		Counterbore Dim F		Standard Cap		Replacement Seal Cap			Wt			
	in	mm	in	mm	in	mm	in	mm	in	mm	Diameter in	mm	Depth in	mm	Material	Seal Cap	Brass	Plastic	Steel	lb	kg
A 13183	1/2		5/8		1.81	46	1.50	38	4.64	118	.504	12.80	.375	9.53	Steel	A 04566	A 16474	P 34627	A 04566	0.58	0.26
A 13220	1/2		1/2		1.81	46	1.31	33	4.11	104	.504	12.80	.375	9.53	Steel	A 04566	A 16474	P 34627	A 04566	0.69	0.31

NPTFE Inlet to Solder

Part Number	NPTFE A		Solder B		C		D		E		Counterbore Dim F				Standard Cap		Replacement Seal Cap			Wt	
	in	mm	in	mm	in	mm	in	mm	in	mm	Diameter		Depth		Material	Seal Cap	Brass	Plastic	Steel	lb	kg
											in	mm	in	mm							
A 13977	1/2	13	1/2	13	1.81	46	1.00	25	4.11	104	.504	12.80	.375	9.53	Steel	A 04566	A 16474	P 34627	A 04566	0.45	0.20
A 13978	1/2	13	5/8	17	1.80	46	1.00	25	4.70	119	.504	12.80	.375	9.53	Steel	A 04566	A 16474	P 34627	A 04566	0.55	0.25
A 13979	3/4	19	7/8	22	2.10	53	1.00	25	6.02	153	.754	19.15	.625	15.88	Plastic	P 34632	A 16474	P 34627	A 04566	1.24	0.56






Solder to Solder

Part Number	A		B		C		D		E		Standard Cap		Replacement Seal Cap			Packing Kit	Wt	
	in	mm	in	mm	in	mm	in	mm	in	mm	Material	Seal Cap	Brass	Plastic	Steel		lb	kg
A 17506	5/8	17	5/8	17	0.91	23	1.00	25	4.20	107	Steel	A 04566	A 16474	P 34627	A 04566	A 17420	0.66	0.30
B 32080	7/8	22	7/8	22	2.28	58	1.75	44	6.20	157	Plastic	P 34632	A 16474	P 34632	A 04566	A 17420	0.99	0.45



Features:

- Maximum abnormal pressure (MAP): 700 psig, 48 bar
- Continuous operating temperature (COT): -40°F/300°F, -40°C/149°C
- Compatible with all CFC, HCFC and HFC refrigerants and oils
- UL/cUL Recognized, Conforms to Pressure Equipment Directive 97/23/EC
- Forged brass body
- Corrosion resistant stem suitable for refrigerants and other industrial fluids


Flare to NPTFE

Internal Swivel Fl x Fl

NPTFE Inlet to Flare

NPTFE x NPTFI

Solder to Flare

Flare to NPTFE

Part Number	Flare A	NPTFE B		C		D		E		Counterbore Dim F				Standard Cap		Replacement Seal Cap			Wt	
		in	mm	in	mm	in	mm	in	mm	Diameter	Depth	in	mm	Material	Seal Cap	Brass	Plastic	Steel	lb	kg
A 15073	#	1/4	1/4	0.94	24	1.00	25	2.96	75	.254	6.45	.31	7.87	Steel	A 04566	A 16474	P 34627	A 04566	0.43	0.19

Torque

Pack Gland		Seal Cap	
ft-lb	N-m	ft-lb	N-m
8 - 12	11 - 16	20 - 30	27 - 41

Internal Swivel Flare to Flare

Part Number		Flare A	Flare B	C		D		E		Torque				Standard Cap		Replacement Seal Cap			Wt	
										Pack Gland		Seal Cap		Material	Seal Cap	Brass	Plastic	Steel	lb	kg
										ft-lb	N-m	ft-lb	N-m							
B 33803	**	1/4	1/4	1.47	37	1.06	27	3.90	99	8 - 12	11 - 16	6 - 10	8 - 14	Steel	A 04566	A 16474	P 34627	A 04566	0.34	0.16
A 17429	***	1/4	1/4	1.47	37	1.06	27	3.49	89	8 - 12	11 - 16	inger Tight	inger Tight	Plastic	P 34627	A 16474	P 34627	A 04566	0.23	0.10
B 34247	****	1/4	1/4	1.47	37	1.06	27	3.90	99	8 - 12	11 - 16	20 - 30	27 - 41	Brass	A 16474	A 16474	P 34627	A 04566	0.34	0.16
A 17474	**	3/8	3/8	1.52	39	1.12	28	3.55	90	8 - 12	11 - 16	6 - 10	8 - 14	Steel	A 04566	A 16474	P 34627	A 04566	0.27	0.12
B 34261	****	3/8	3/8	1.52	39	1.12	28	3.55	90	8 - 12	11 - 16	20 - 30	27 - 41	Brass	A 16474	A 16474	P 34627	A 04566	0.42	0.19

NPTFE Inlet to Flare

Part Number	NPTFE A	Flare B	C		D		E		Counterbore Dim F				Standard Cap		Replacement Seal Cap			Wt	
	in	in mm	in	mm	in	mm	in	mm	Diameter in	mm	Depth in	mm	Material	Seal Cap	Brass	Plastic	Steel	lb	kg
A 11031	1/4	1/4	1.00	25	0.94	24	3.02	77	.254	6.45	.31	7.87	Steel	A 04566	A 16474	P 34627	A 04566	0.28	0.13
A 16472 *	1/4	1/4	1.00	25	0.94	24	3.02	77	.254	6.45	.31	7.87	Brass	A 16474	A 16474	P 34627	A 04566	0.29	0.13
A 11030	1/4	3/8	1.06	27	1.12	28	3.10	79	.317	8.05	.31	7.87	Steel	A 04566	A 16474	P 34627	A 04566	0.25	0.11
B 33964 ###	1/4	1/4	1.00	25	0.94	24	3.02	77	.254	6.45	.31	7.87	Steel	A 04566	A 16474	P 34627	A 04566	0.31	0.14
A 13613	3/8	1/4	1.12	28	1.06	27	3.14	80	.379	9.63	.31	7.87	Steel	A 04566	A 16474	P 34627	A 04566	0.48	0.22
A 13503	3/8	3/8	1.12	28	1.12	28	3.15	80	.379	9.63	.5	12.70	Steel	A 04566	A 16474	P 34627	A 04566	0.34	0.15
A 11042	3/8	1/2	1.38	35	1.38	35	3.77	96	.379	9.63	.31	7.87	Steel	A 00409				0.51	0.23

NPTFE x NPTFI, NPTFI x NPTFE

Part Number		A	B	C		D		E		Torque		Standard Cap		Replacement Seal Cap			Wt	
		in	in	in	mm	in	mm	in	mm	Pack Gland ft-lb	N-m	Material	Seal Cap	Brass	Plastic	Steel	lb	kg
A 13502	NPTFE X NPTFI	1/4	1/4	1.38	35	1.06	27	3.78	96	8 - 12	11 - 16	Steel	A 00409				0.49	0.22
B 32222	NPTFI X NPTFE	1/4	1/4	1.25	32	1.12	28	3.64	92	8 - 12	11 - 16	Steel	A 00409				0.51	0.23

Solder to Flare

Part Number ^	Solder	Flare B in	C in	D mm	E mm	F ODE in	mm	in	mm	Torque				Standard Cap		Replacement Seal Cap			Wt			
										Pack Gland		Seal Cap		Material	Seal Cap	Brass	Plastic	Steel	lb	kg		
										ft-lb	N-m	ft-lb	N-m									
A 17502	**	1/4	1/4	0.71	18	1.03	26	2.75	70	3/8	10	8 - 12	11 - 16	6 - 10	8 - 14	Steel	A 04566	A 16474	P 34627	A 04566	0.30	0.14
B 34252	***	1/4	1/4	0.71	18	1.03	26	2.75	70	3/8	10	8 - 12	11 - 16	20 - 30	27 - 41	Brass	A 16474	A 16474	P 34627	A 04566	0.31	0.14
B 35161	###	1/4	1/4	0.71	18	1.03	26	2.75	70	3/8	10	8 - 12	11 - 16	6 - 10	8 - 14	Steel	A 04566	A 16474	P 34627	A 04566	0.31	0.14
A 17503	**	3/8	3/8	0.69	18	1.50	38	2.72	69	1/2	13	8 - 12	11 - 16	6 - 10	8 - 14	Steel	A 04566	A 16474	P 34627	A 04566	0.49	0.22
B 34255	***	3/8	3/8	0.69	18	1.27	32	2.72	69	1/2	13	8 - 12	11 - 16	20 - 30	27 - 41	Brass	A 16474	A 16474	P 34627	A 04566	0.37	0.17
B 35160	###	3/8	3/8	0.69	18	1.50	38	2.72	69	1/2	13	8 - 12	11 - 16	6 - 10	8 - 14	Steel	A 04566	A 16474	P 34627	A 04566	0.38	0.17
B 34288	***	3/8	3/8	0.69	18	1.50	38	2.72	69	1/2	13			FT	FT	Plastic	P 34627	A 16474	P 34627	A 04566	0.31	0.14

Machined to accept OD size tube as indicated.

Steel Seal Cap, Loosely Assembled

Cap finger tight for shipping

* Brass Seal Cap

** Steel Seal Cap

*** Plastic Seal Cap

**** Brass Seal Cap, includes copper gasket

^ 3/8 Solder also 1/2 FTG

^ 1/4 Solder also 3/8 FTG