PARTS & ACCESSORIES FOR MINI-SPLITS

INTERCONNECTING WIRES (LINE) INTERCONNECTING WIRES

- 16/4 STRANDED BC SHIELDED CMP 16/4 STR COMPACT 250'R BLK
- 16/4 STR COMPACT 50'R BLK
 22/4 STR SHIELDED CMP
 14/4 STRANDED BC SHIELDED CMP

PART NO	PURPOSE	SPECS	DESCRIPTION	PRODUCT
ICW-1	Outdoor/Indoor interconnecting wire	16/4 AWG CMP Plenum Multi-Conductor Shielded Wire, Sold by the foot	Mini-Split 16/4 AWG Stranded and Shielded wire strongly recommended for interconnecting Outdoor and Indoor units.	
ICW-2	Outdoor/Indoor interconnecting wire	16/4 AWG Bare Copper Power and Control Cable, Sold by the foot	Mini-Split 16/4 Stranded wire for interconnecting signal between Outdoor and Indoor unit, for residential applications where interference is not critical.	
ICW-3	Outdoor/Indoor interconnecting wire	22/4 AWG CMP Plenum Multi-Conductor Shielded Wire, Sold by the foot	Mini-Split 22/4 AWG Stranded and Shielded wire strongly recommended for interconnecting CHP024CD-B(0) Outdoor with CCA-24, FCA-24, TCA-24 Evaporators.	
ICW-4	Outdoor/Indoor interconnecting wire	14/4 AWG CMP Plenum Multi – Conductor Shielded Wire	Mini-Split 14/4 AWG Stranded and Shielded wire strongly recommended for interconnecting Outdoor and Indoor units.	

REMOTE CONTROL FOR (ALL BRANDS) MINI-SPLITS

SMART ELECTRIC REMOTE CONTROL: Thousands of codes available to match up to 4,000 different types of Mini-splits. Simply locate a matching code for your Mini-split brand on the list available, then using the Remote Control point at the evaporator unit and follow the Instructions on the manual. After programming the Remote Control successfully, your system is ready to operate.

FEATURES:

- 4000 different codes compatible with multiple air conditioning equipment brands
- No programming necessary for several recognizable air conditioning brands
- User-friendly Auto-Search Code function
- Energy-Saving Feature (Sleep Function)

- Clock Settings and 24-Hr On-Off timer
- General Lock Function to prevent undesired program ming changes
- Bright LCD display
- Memory Function: settings are not lost during battery change-out
- °F Display and °C Display settings



REMOTE CONTROL FOR (ALL BRANDS) MINI-SPLITS

PART NO	DESCRIPTION	
CU5000	Fahrenheit/Celsius remote	

