

UHS UNIVERSAL HUMIDIFIER SOLENOID VALVE REPLACEMENT KITS



- Each Kit Includes Solenoid Valve, Mounting Bracket and All Fittings to Remove and Replace the Existing Solenoid Valve
- Easy "Wrench-in" Installation
- Adjustable Water Flow Valve
- Time Saving
- Universal Replacement Reduces Inventory
- Economically Priced Compared to OEM Versions

Part No.	Volts	Replaces
SUHS24	24 V	Aprilaire® 4040, General® 990-53, Honeywell® 320016939-002, Skuttle® A01-0814-148
UHS120	120 V	Aprilaire® 4005, General® 990-52

NEOPRENE AIR TUBING



- Temperature Range: 0°F to 160°F (-17°C to 71°C)
- Pressure Range: -20 to 20 in. W.C.

Part No.	Dimensions	Length
SNAT3165	3/16" ID	5 ft.
SNAT316100	3/16" ID	100 ft.
SNAT185	1/8" ID	5 ft.

SILICONE AIR TUBING



- NSF 51, Soft, Red
- Temperature Range: -100°F to 500°F (-73°C to 260°C)
- 5 Foot Rolls

Part No.	Dimensions	Working Pressure	Burst Pressure
SSRT185	1/8" ID x 5/16" OD	25 psi	75 psi
SSRT3165	3/16" ID x 5/16" OD	20 psi	60 psi
SSRT145	1/4" ID x 3/8" OD	5 psi	15 psi

TR10 TEFLON O-RING KIT



- Package of 12 O-Rings
- 3 of Each Size

OD Size	ID Size
9/16"	7/16"
3/4"	5/8"
1"	7/8"
1 1/2"	1 3/8"

GB10 FINNY'S GASKET BOOK



- Replacements for Gaskets in Expansion and Solenoid Valves and Pumps
- 36 Different Gaskets Replace Most Common Gaskets Used Today
- Garlock Material Replaces All Older Materials