

H.P.	Volts	Amps	RPM	Spd.	Model	Fig.	Type	Mtg.	Dia.	Rot.	"A" Dim	Shaft Dia. and Length	Reference No.
RHEEM/RUUD (continued)													
1/3-1/4	208-230	2.3/1.6	825	2	D815 ■▲	J	PSC	Bracket	5.6	C.W.	4-1/2	1/2 x 2-1/3	51-23103-07
1/5	208-230	1.3	1075	1	D2840^	F	PSC	Stud	5.6	C.W.	3-3/4	1/2 x 4-1/8	51-21853-82
1/6	208-230	1.2	825	1	D2842^	E	PSC	Stud	5.6	C.W.	4	1/2 x 4-1/4	51-20760-11
1/8	208-230	1.1	825	1	D832^	A	PSC	Stud	5.6	Rev.	4	1/2 x 4-3/4	21276-02 21276-01 512076-01
1/10	208-230	.8	825	1	D2844 †▲	E	PSC	Stud	5.6	C.W.	3-3/4	1/2 x 4-1/4	51-20761-11
1/15	230/460	1.2, 0.6	3000	1	D459•	H	SP	Stud	3.3	C.W.	7	1/4 x 3	HC24AU725A, JB1P044 AB1S078, JB1R039 AB1S029, S88-556
1/200	208-230	.25	3000	1	K628	C	SP	Bracket	—	C.W.	4.9	1/4 x 1-1/2	51-21964-01, 7102-0628
79CFM	115	1.1	3000	1	A079	B	SP	—	—	C.C.W.	—	—	74-70-21504-03-04 74-70-21496-03-01 JAIM106, JAIM137, 7021-5615
86CFM	115	1.3	3200	1	A086	D	SP	—	—	C.W.	—	—	7021-5990
90CFM	115	1.1	3000	1	A090	G	SP	—	—	C.W.	—	—	RHEEM 70-21496-01 7021-5239, JA1M102
—	115	0.75	3450	1	A136@	K	PSC	—	3.3	C.W.	—	—	RHEEM, 7062-3861
—	115	0.95	3000	1	A139	L	SP	—	3.3	C.W.	—	—	RHEEM, 7021-7577
—	115	0.7	3450	1	A142+	M	PSC	—	3.3	C.W.	—	—	RHEEM, 7062-1881
REZNOR													
1/8	480	.32	3200	1	D461	I	PSC	Stud	3.3	C.C.W.	4-1/4	5/16 x 3-1/3	7162-0396

D2840 Use 3M 370V for 208-230V applications and 5M 370V for 200V applications.

D2842 Use 5M 370V for 208-230V applications and 7.5M 370V for 200V applications.

† 3M 370V

^ Has 4 drilled and tapped holes in shell.

▲ 10M 370V capacitor not included

+ Capacitor included, 4MFD, 370 VAC

• Ball bearing

■ Includes 8 drilled and tapped holes in shell

@ Capacitor not included; capacitor rating 4MFD, 370 VAC

NOTE: Rotation is determined by looking at shaft end. Shaft length is measured from motor face.



Fig. A D832



Fig. D A086



Fig. G A090



Fig. J D815



Fig. M A142



Fig. B A079



Fig. E D2842, D2844



Fig. H D459



Fig. K A136



Fig. C K628




Fig. F D2840



Fig. I D461



Fig. L A139



Products on this page are NOT SUITABLE for unattended equipment unless indicated by ► symbol. See inside back cover for additional information.

PSC motors use 5M 370V capacitors unless otherwise indicated.