

| H.P.                                       | Volts   | Amps               | RPM  | Spd. | Model   | Fig. | Type | Mtg.      | Dia. | Rot. | "A"<br>Dim | Shaft Dia.<br>and Length | Reference No.                                                                              |
|--------------------------------------------|---------|--------------------|------|------|---------|------|------|-----------|------|------|------------|--------------------------|--------------------------------------------------------------------------------------------|
| <b>PATTON</b>                              |         |                    |      |      |         |      |      |           |      |      |            |                          |                                                                                            |
| 1/4-1/12                                   | 115     | 3.2-2.4            | 1100 | 2    | D824#   | B    | PSC  | Pedestal  | 5.6  | C.W. | 5-3/4      | 1/2 x 3-1/2              | 7126-0485, 7126-0922                                                                       |
| <b>PENN VENTILATOR</b>                     |         |                    |      |      |         |      |      |           |      |      |            |                          |                                                                                            |
| ▶ 1/15                                     | 115     | 2.3                | 1050 | 1    | D342 †  | A    | SP   | Stud      | 5.0  | C.W. | 2-5/8      | 3/8 x 2                  | 7151-3081, 7151-3565                                                                       |
| ▶ 1/20                                     | 115     | 2.0                | 1045 | 1    | D1036   | A    | SP   | Band Stud | 5.0  | C.W. | 2-3/8      | 3/8 x 2-1/8              | 7151-2139<br>ROOF TOP VENT<br>Z8                                                           |
| <b>PMI/VALCUN HART</b>                     |         |                    |      |      |         |      |      |           |      |      |            |                          |                                                                                            |
| —                                          | 115     | 0.7                | 3450 | 1    | A142#   | F    | PSC  | —         | 3.3  | C.W. | —          | —                        | 7062-2513                                                                                  |
| <b>RHEEM/RUUD (continued on next page)</b> |         |                    |      |      |         |      |      |           |      |      |            |                          |                                                                                            |
| 3/4-1/2-1/3-1/4                            | 115     | 9.5-7.2<br>5.6-3.5 | 1075 | 4    | D724 ■▲ | E    | PSC  | Brkt      | 5.6  | Rev. | 5-3/4      | 1/2 x 6                  | Various                                                                                    |
| 1/2-1/3-1/4-1/5                            | 115     | 7.3                | 1075 | 4    | D806 ■  | E    | PSC  | Brkt      | 5.6  | Rev. | 4-3/4      | 1/2 x 3-3/4              | 51-23012-41                                                                                |
| 1/2-1/3                                    | 208-230 | 4.0-2.8            | 1075 | 2    | D831 ‡  | C    | PSC  | Band      | 5.6  | D.S. | 6-3/4      | 7-1/8 x 1/2 x 7-1/8      | Marathon X231, Leece<br>Neville RE128, Amana,<br>Rheem/Ruud, Luxaire,<br>American Standard |
| NEW 1/2                                    | 208-230 | 2.9                | 1075 | 1    | D2800 ^ | G    | PSC  | Stud      | 5.6  | Rev. | 5          | 1/2 x 5                  | K55HXYMC-4445,<br>51-23052-11                                                              |
| 1/3                                        | 208-230 | 2.0                | 1075 | 1    | D2834 ^ | D    | PSC  | Stud      | 5.6  | C.W. | 4          | 1/2 x 4-1/4              | 51-21853-83                                                                                |

**D2800** Use 7.5M 370V for 230V applications and 10M 370V for 208V applications.

**D2834** Use 5M 370V for 208-230V applications and 7.5M 370V for 200V applications.

† Mounts on (3) P/N 0061-1518 Coleman Mounts

• Ball bearing motor

‡ 7.5M 370V

# 4M 370V capacitor

^ Has 4 drilled and tapped holes in shell.

■ Has 8 drilled and tapped holes in shell.

▲ 15M 370V capacitor

**NOTE:** Rotation is determined by looking at shaft end. Shaft length is measured from motor face.



**Fig. A** D324, D1036



**Fig. C** D831



**Fig. E** D724, D806



**Fig. G** D2800




**Fig. B** D824



**Fig. D** D2834



**Fig. F** A142



Products on this page are NOT SUITABLE for unattended equipment unless indicated by ▶ symbol. See inside back cover for additional information.

PSC motors use 5M 370V capacitors unless otherwise indicated.